



Aspen10 MAKES A SENSOR IOT CLOUD CONNECTED

.....



Edge Device for a Single Sensor

The revolutionary Aspen™10 Internet of Things (IoT) Edge Device allows users to easily connect their environmental sensor to the cloud. It is rugged and durable and may be mounted outdoors without the need for a second enclosure. It has an integrated solar panel and internal rechargeable battery, making the Aspen10 a truly self-sustaining device.

The Aspen10 is also small and compact, which makes it easy to install in a variety of locations without disturbing the environment it is monitoring. An integrated IoT cellular modem allows the Aspen10 to transmit data to the cloud, and a global positioning system (GPS) receiver provides automated installation location.

Setting up the Aspen 10 to read your sensor is quick and easy thanks to a new sensor interface technology, AQWire, that allows automatic identification of any sensor with an SDI-12 or one-wire identification. The Aspen10 publishes this ID to the cloud, in return receiving a customized measurement configuration and program for your specific sensor and application. You can then monitor your data from anywhere. internal rechargeable battery, making the Aspen10 a truly self-sustaining device.

The Aspen10 is also small and compact, which makes it easy to install in a variety of locations without disturbing the environment it is monitoring. An integrated IoT cellular modem allows the Aspen10 to transmit data to the cloud, and a global positioning system (GPS) receiver provides automated installation location.

Setting up the Aspen10 to read your sensor is quick and easy thanks to a new sensor interface technology, AQWire, that allows automatic identification of any sensor with an SDI-12 or one-wire identification. The Aspen10 publishes this ID to the cloud, in return receiving a customized measurement configuration and program for your specific sensor and application. You can then monitor your data from anywhere.

Benefits and Features:

- IoT device using local cellular networks as the low-power wide-area network (LPWAN)
- Cellular CAT M1 for worldwide roaming
- Geolocation to automatically determine the edge device's location
- Solar charging to keep the IoT device operational indefinitely using just a few hours of daily sunlight
- Internal rechargeable LiFePO4 battery with reserve power for more than one month's operation without charge for all supported sensors
- Smart sensor detection and identification (AQWire)
- Smart sensor power automatic optimization for the attached sensor.

Aspen10

Detailed Description:

The Aspen10 is a multipurpose, compact, entry-level edge device with a simple plug-and-play interface. Supported sensors measure hydrological, meteorological, environmental, and industrial phenomena. The Aspen10 is part of the IoT and makes sensor data accessible anywhere via the Aspen10's compatibility with the MQTT protocol and its integration with MUNRO Cloud. The Aspen 10 provides maintenance-free sensor power and automates cellular connectivity, data storage, and data forwarding to MUNRO Cloud, where users can both visualize their data and manage API access.

The Aspen10 is similar to a full MUNRO system and comprises a data logger, wiring terminals, enclosure, solar panel, charge regulator, battery, modem, and antenna—all in one small package.

Compatible sensors are cabled using the AQWire standard. A detect pin lets the Aspen10 know that it has connected to a sensor with either an SDI-12 or one-wire capability of self-identification. After identifying the sensor, the Aspen 10 connects to MUNRO Cloud to retrieve the appropriate configuration and program for that sensor, which enable the edge device to power the sensor appropriately and make accurate analog or digital measurements.

A free app, MUNRO Go, enables secure NFC/Bluetooth pairing between a phone and the Aspen10. This greatly simplifies the installation process with real-time sensor readings, diagnostic tools, & data-to-cloud delivery information while you are on-site. This gives you confidence that everything is working from end to end before leaving the installation site. All of this allows you to collect data from the selected sensor in the location you need from practically anywhere on the globe.

Technical Specifications

Processor	32-bit arm cortex (CPU)
Memory	• 2 MB flash • 640 KB SRAM
Program Execution Period	1 s to 1 day; 1 s increments
Real-Time Clock Resolution	±1 s
Real-Time Clock Accuracy	Synchronized with MUNRO Cloud once per day
Operating Temperature Range	• -20 to +60°C(standard) • -40 to +75°C(extended) • Outdoor environment
Maximum Scan Rate	1 s
Analog Inputs	Up to 2 single-ended or 1 differential can be programmed for a variety of analog inputs. Pulse and digital I/O functions are also supported.
Communication Protocols	SDI-12, HTTP(S), MQTT
Case Material	• High-impact-resistant and UV-resistant ASA, recycle code 7 • IP65 water-resistant rated, Gore-Tex breathability
Digital I/O	Terminals are configured for SDI-12.
Certifications	CB Certificate Number NO127343
Dimensions	16.2 x 8.0 x 5.8 cm (6.4 x 3.2 x 2.3 in.)
Weight	• 395 g (0.9 lb) for -ST option • 352 g (0.8 lb) for -XT option
POWER	
Battery	Note: Charge and discharge characteristics are controlled internally according to battery type.
Battery for -20° to +60°C (-ST) Option	3.2 Vdc, 7.2 Ah, Li-Po PHD26650
Battery for -40° to +75°C (-XT) Option	3.65 Vdc, 5.6 Ah, Li-ion Saft MP176065 xtd
Average Current Drain	<ul style="list-style-type: none"> • <0.35 μA (deep sleep) • <1 mA (idle) • 10 μA (ultra-low power) for 5 Vdc sensor power supply • 5 mA for 5 Vdc sensor power supply • 14.3 mA for 8 Vdc sensor power supply • 30 mA for 12 Vdc sensor power supply.

Aspen10

Technical Specifications

POWER OUTPUT	
Note	Regulated 5, 8, or 12 Vdc (disabled when battery capacity <0.5 Ah)
5 Vdc Current Limit	• 30 mA (ultra-low power) • 210 mA
8 Vdc Current Limit	210 mA
12 Vdc Current Limit	210 mA
COMMUNICATIONS	
Protocols	SDI-12
Internet Protocols	HTTP(S), MQTT
Near Field Communication (NFC)	Target device compatible with us
Bluetooth Low Energy (BLE)	• Compatible with us • Maximum distance of 50 m (165 ft)
SDI-12	One SDI-12 compliant terminal meets SDI-12 Standard v 1.4